US009547394B2

(12) **United States Patent**
Hotelling et al.

(10) **Patent No.:** **US 9,547,394 B2**
(45) **Date of Patent:** **Jan. 17, 2017**

(54) **MULTIPOINT TOUCH SURFACE CONTROLLER**

(75) Inventors: **Steven Porter Hotelling**, San Jose, CA (US); **Christoph Horst Krah**, Los Altos, CA (US); **Brian Quentin Huppi**, San Francisco, CA (US)

(73) Assignee: **Apple Inc.**, Cupertino, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1133 days.

(21) Appl. No.: **12/549,229**

(22) Filed: **Aug. 27, 2009**

(65) **Prior Publication Data**

US 2009/0315850 A1 Dec. 24, 2009

Related U.S. Application Data

(62) Division of application No. 11/381,313, filed on May 2, 2006.

(51) **Int. Cl.**
G06F 3/044 (2006.01)
G06F 3/041 (2006.01)

(52) **U.S. Cl.**
CPC *G06F 3/044* (2013.01); *G06F 3/0418* (2013.01)

(58) **Field of Classification Search**
USPC 345/173–178; 327/50–57, 292; 250/214
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,333,160 A	7/1967	Gorski	
3,541,541 A	11/1970	Englebart	

3,662,105 A	5/1972	Hurst et al.	
3,798,370 A	3/1974	Hurst	
4,246,452 A	1/1981	Chandler	
4,476,463 A	10/1984	Ng et al.	
4,511,760 A	4/1985	Garwin	
4,543,564 A	9/1985	Audoin et al.	
4,550,221 A	10/1985	Mabusth	
4,672,364 A	6/1987	Lucas	
4,672,558 A	6/1987	Beckes et al.	
4,692,809 A	9/1987	Beining et al.	
4,695,827 A	9/1987	Beining et al.	
4,733,222 A	3/1988	Evans	
4,734,685 A	3/1988	Watanabe	

(Continued)

FOREIGN PATENT DOCUMENTS

CA	1243096	10/1988
DE	102 51 296	5/2004

(Continued)

OTHER PUBLICATIONS

GB Combined Search and Examination Report mailed Mar. 21, 2011, for GB Application No. 1101918.9, filed Oct. 24, 2008, four pages.

(Continued)

Primary Examiner — Jonathan Horner
(74) *Attorney, Agent, or Firm* — Morrison & Foerster LLP

(57) **ABSTRACT**

A multipoint touch surface controller is disclosed herein. The controller includes an integrated circuit including output circuitry for driving a capacitive multi-touch sensor and input circuitry for reading the sensor. Also disclosed herein are various noise rejection and dynamic range enhancement techniques that permit the controller to be used with various sensors in various conditions without reconfiguring hardware.

22 Claims, 12 Drawing Sheets